

ENGLISH ▼



SNP-6321H

DELETE ○



PNM-9081VQ

DELETE ○



XNO-6120R

DELETE ○



XNP-6320H

DELETE ○

DESCRIPTION	<p>The SNP-6321H is a PTZ dome camera that provides 32x zoom at 2 megapixel Full HD resolution. This outdoor PTZ dome camera has the ability to zoom in with perfect clarity at an incredible speed allowing you to track your evidence while capturing smooth video. Includes 32 privacy zones with zoom threshold to ensure privacy without obscuring general surveillance. Advanced features include WDR, Intelligent Video Analytics, defog, on-screen compass directions, & SDXC memory card support. Powered by PoE+ for easy installation or 24v AC for ultra-low temperature environments.</p>	<p>Network vandal outdoor Multi-sensor Multi-Directional dome camera, (5MP X 4 sensors) 20MP @ 30fps WDR off/on, motorized vari-focal Lens 2.6x (3.6 ~ 9.4mm) (102.5° ~ 38.7°), triple Codec H.265/H.264 /MJPEG with WiseStream II technology, 120dB WDR, Defocus detection, built in analytics, true D/N, 4x SD card, hallway view, HLC, Defog detection, DIS(Gyro sensor), 12VDC/HPoE (power adaptor is included), IP66/IK10, -40°C ~ +55°C (-40°F ~ +131°F)</p>	<p>Wisenet X powered by Wisenet 5 network IR outdoor bullet camera, 2MP, Full HD(1080p) @60fps WDR off/on(120dB) or @30fps WDR on(150dB), 12X optical zoom lens (5.2mm ~62.4mm) (54.58° ~ 5.30°), H.265/H.264 /MJPEG, WiseStream II compression technology, 150dB WDR, USB port for easy installation, advanced video analytics and sound classification, high powered IR LEDs range of 229', true D/N, dual SD card, hallway view, HLC, defocus detection, DIS, 12VDC/24VAC/PoE, IP67, IK10, NEMA 4X, built-in -40°F heater</p>	<p>Wisenet X series features our Wisenet 5 chipset, 2MP resolution, Full HD(1080p) @ 60fps, 32X optical zoom lens (4.44mm ~142.6mm) (61.8° ~ 2.19°), Pan: 360° endless. Tilt: -15°~ 195°, triple codec H.265/H.264/MJPEG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics and sound classification, true D/N, dual SD card, HLC, defog detection, DIS(Gyro),24VAC/PoE+, IP66/IK10, temperature range from -58°F ~ +131°F</p>
SHORT DESCRIPTION	2MP HD 32x Network Outdoor PTZ Dome Camera	20MP Multi-sensor, multi-directional camera	2MP Network IR 12X optical zoom bullet camera	Network Outdoor PTZ camera

 **Technical Support**

ENGLISH ▾

		MJPEG	MJPEG	
DAY/NIGHT	IR Cut Filter	IR Cut Filter	IR Cut Filter	
CAMERA SYSTEM	Network	Network	Network	
CAMERA SERIES	Wisenet III	P series	X series	
CAMERA TYPE	PTZ	Multi-sensor	Bullet	
MAX RESOLUTION	2 Megapixel / Full HD	20 Megapixel	2 Megapixel / Full HD	
MAX FRAME RATE (H.264)	60fps @ 2MP	30fps @ 20MP	60fps @ 2MP	
AUDIO SUPPORT	Bi-directional Audio	No	Bi-directional Audio	
SD CARD SLOT	Single SD Card	Four SD Card Slots	Dual SD Cards	
LENS TYPE	Zoom	Motorized Vari-Focal	Zoom	
WDR	Yes	Yes	Yes	
ADVANCED ANALYTICS	Audio Detection, Defog, Enter / Exit, Face Detection, Object Appear/Disappear, Virtual Line	Defog, Directional Detection, Enter / Exit, Face Detection, Fog Detection, Loitering, Object Appear/Disappear, Virtual Line	Audio Classification, Audio Detection, Defog, Directional Detection, Enter / Exit, Face Detection, Fog Detection, Loitering, Object Appear/Disappear, Virtual Line	
IR	No	No	Yes	
WISESTREAM	No	Yes	Yes	
DIS	Yes	Yes	Yes	
MOBILE	No	No	No	
INSTALLATION OUTPUT	Yes	Yes	Yes	
USB INSTALLATION	No	No	Yes	
INDOOR / OUTDOOR	Outdoor	Outdoor	Outdoor	



ENGLISH ▼

IMPACT RATING	Yes	Yes	Yes	
INGRESS PROTECTION	IP66	IP66	IP67	
HLC	No	Yes	Yes	

COMPANY

ABOUT

TRADE SHOWS & EVENTS

CONTACTS

SUBSCRIBE FOR UPDATES

SALES

NORTH AMERICA SALES REGION

MANUFACTURER
REPRESENTATIVES

HANWHA STRATEGIC
DISTRIBUTORS

MAP POLICY

OUR BRAND

BLOG

EMPLOYMENT OPPORTUNITIES



